DS-3500

Color LCD Display | Full Workflow Integration | 256-Bit Encryption Rate

Easy-to-use digital recording and editing for professionals.

Dictation Defined.





The DS-3500 Professional Dictation System digital voice recorder is designed to dramatically increase efficiency and streamline operations in any professional environment. Packed with premium features and intuitive controls, it's easily manageable, secure and absolutely mobile – the ideal device wherever the job might take you.



The perfect blend of premium features and ease of use.

DS-3500

- Easy operation via push buttons
- Full integration into professional workflows possible
- Perfect for recording conferences and interviews in stereo (with external microphones)

Enhanced security.

Device password protection and DSS Pro real-time 128- or 256-bit file encryption makes the DS-3500 ideal for workplace environments that deal with sensitive information.

Endless flexibility.

A vast array of functions and accessories, audio codes and indexing options, as well as support for multiple work types and users, makes the DS-3500 customizable enough to suit any purpose in any IT environment. The ODMS software is compatible with Microsoft Windows 7, Vista and XP and Mac OS X.

Superior sound qulaity.

The DS-3500's redesigned, speech-optimized microphone is independently housed for flawless sound reproduction. It's the only Olympus Professional Dictation device to support DSS/DSS Pro, WAV and MP3 recording formats





Kilpatrick Equipment Company

DALLAS

2612 Manor Way, Dallas, TX 75235 Ph 214-358-4346 / 800-929-2822 Fax 214-358-3723

HOUSTON

3311 Richmond Ave #206, Houston, TX 77098 Ph 713-979-1534 / Fax 214-358-3723



olympusamericaprodictation.com



OlympusProDictation



DS-3500 | Professional Dictation

D3-3300 Professional Dictation	
Recording format	DS2 (Digital Speech Standard Pro)
Internal memory	SD-card: 512 MB to 32 GB
External memory	SD card (SD/SDHC/SDXC) up to 64GB
Frequency reponse (internal microphone)	QP mode: 148 hours SP mode: 303 hours
Input Level	-70 dBv
PC Interface	USB
LCD	Large LCD screen with backlight
LED	Yes
Folders Messages	5 folders/200 messages per folder
Sampling Frequency	QP: 16 khz/28 kbps SP: 12 kHz/13.7 kbps
Overall Frequency Response	QP: 200 - 7,000 Hz SP: 200 - 5,000 Hz
LP Mode	Yes
Voice-activated recording	Yes
Play sync recording	Yes
Demographic Data Input	Yes
Practical Maximum Output	250 mW
Write Protection	Yes
Speaker	Built-in o23mm round dynamic speaker
Microphone Jack	3.5 mm mini-jack, 2 k Ω ,
Earphone Jack	3.5 mm mini-jack, 8Ω or more
Batteries	Rechargeable LI-42B: li-ion- battery (710mAh) Up to 26 hours of recording time with one battery charge
External Power Supply	No
Battery Life	Recording: (rechargeable batteries) QP mode: Approximately 30 hours SP mode: Approximately 37 hours Playback: All modes: Approximately 35 hours
Dimensions	4.47 x 1.97 x 0.67 in. (113.5 x 50.0 x 17 mm), without protrusions
Weight	3.7 oz (105 g), including alkaline batteries
OS Supported	MicrosoftR WindowsR XP: Professional / Home Edition SP3 x86 Professional / Home Edition SP2 x64 MicrosoftR Windows VistaR: Ultimate / Enterprise / Business / Home Premium / Home Basic SP2 (both x86/64) MicrosoftR Windows 7R: Ultimate / Enterprise / Professional / Home Premium (both x86/64) Ultimate / Enterprise / Professional / Home Premium SP1 (both x86/64) Mac OS X 10.4.11 - 10.7
CPU	Windows: MicrosoftR WindowsR XP / Vista / 7: 1 GHz or higher Macintosh: PowerPCR G3 500 MHz or more, or Intel Core Solo/Duo 1.5 GHz or more
RAM	Windows: MicrosoftR WindowsR XP: 256 MB or more MicrosoftR Windows VistaR:1 GB or more MicrosoftR Windows 7R:1 GB or more (32 bit) / 2 GB or more (64 bit) Macintosh: 256 MB or more (512 MB or more is recommended)
Video Card and Display	Windows: 800 x 600 pixels or more, 65,536 colors or more (16,770,000 colors or more is recommended) Macintosh: 1024 x 768 pixels or more, 32,000 colors or more
Removable Drive	CD or DVD drive
USB Port	At least one free USB port