

DS-7000

Color LCD Display | Full Workflow Integration | 256-Bit Encryption Rate

Easy-to-use
digital recording
and editing for
professionals.
Dictation Defined.



OLYMPUS

Designed for professionals who rely on secure, flexible, reliable products as integral parts of their office workflow, the DS-7000 features real-time 256-bit file encryption, a redesigned, independently housed microphone, enhanced battery life and next-generation Olympus Dictation Management Systems (ODMS) software.



The power of speech: easy, mobile and secure.

DS-7000

- Precise slide switch for full control in your palm
- Speech-optimized microphone
- Full integration into professional workflows possible
- Up to 200 customized dictation tags selectable

Enhanced security.

Device password protection and DSS Pro real-time 128- or 256-bit file encryption makes the DS-7000 ideal for workplace environments that deal with sensitive information.

Endless flexibility.

A vast array of functions and accessories, audio codes and indexing options, as well as support for multiple work types and users, makes the DS-7000 customizable enough to suit any purpose in any IT environment. The ODMS software is compatible with Microsoft Windows 7, Vista and XP and Mac OS X.

Superior sound and quality.

The DS-7000's redesigned, speech-optimized microphone is independently housed for flawless sound reproduction. It offers multiple recording modes, as well as two quality levels – QP (16 kHz/28 kbps) and SP (12 kHz/13.7 kbps).



Kilpatrick Equipment Company

DALLAS

2612 Manor Way, Dallas, TX 75235

Ph 214-358-4346 / 800-929-2822

Fax 214-358-3723

HOUSTON

3311 Richmond Ave #206, Houston, TX 77098

Ph 713-979-1534 / Fax 214-358- 3723



olympusamericaprodictation.com



OlympusProDictation



@ProDictation

Recording format	DS2 (Digital Speech Standard Pro)
Internal memory	SD-card: 512 MB to 32 GB
External memory	SD card (SD/SDHC/SDXC) up to 64GB
Frequency response (internal microphone)	QP mode: 148 hours SP mode: 303 hours
Input Level	-70 dBv
PC Interface	USB
LCD	Large LCD screen with backlight
LED	Yes
Folders Messages	5 folders/200 messages per folder
Sampling Frequency	QP: 16 kHz/28 kbps SP: 12 kHz/13.7 kbps
Overall Frequency Response	QP: 200 - 7,000 Hz SP: 200 - 5,000 Hz
LP Mode	Yes
Voice-activated recording	Yes
Play sync recording	Yes
Demographic Data Input	Yes
Practical Maximum Output	250 mW
Write Protection	Yes
Speaker	Built-in ø23mm round dynamic speaker
Microphone Jack	3.5mm mini-jack, 2 kΩ
Earphone Jack	3.5mm mini-jack, 8Ω or more
Batteries	Rechargeable LI-42B : li-ion- battery (710mAh) Up to 26 hours of recording time with one battery charge
External Power Supply	Yes
Battery Life	Recording: (rechargeable batteries) QP mode: Approximately 30 hours SP mode: Approximately 37 hours Playback: All modes: Approximately 35 hours
Dimensions	4.47 x 1.97 x 0.67 in. (113.5 x 50.0 x 17 mm), without protrusions
Weight	3.7 oz (105 g), including alkaline batteries
OS Supported	Microsoft® Windows® XP: Professional / Home Edition SP3 x86 Professional / Home Edition SP2 x64 Microsoft® Windows Vista®: Ultimate / Enterprise / Business / Home Premium / Home Basic SP2 (both x86/64) Microsoft® Windows 7®: Ultimate / Enterprise / Professional / Home Premium (both x86/64) Ultimate / Enterprise / Professional / Home Premium SP1 (both x86/64) Mac OS X 10.4.11 - 10.7
CPU	Windows: Microsoft® Windows® XP / Vista / 7: 1 GHz or higher Macintosh: PowerPC® G3 500 MHz or more, or Intel Core Solo/Duo 1.5 GHz or more
RAM	Windows: Microsoft® Windows® XP: 256 MB or more Microsoft® Windows Vista®: 1 GB or more Microsoft® Windows 7®: 1 GB or more (32 bit) / 2 GB or more (64 bit) Macintosh: 256 MB or more (512 MB or more is recommended)
Video Card and Display	Windows: 800 x 600 pixels or more, 65,536 colors or more (16,770,000 colors or more is recommended) Macintosh: 1024 x 768 pixels or more, 32,000 colors or more
Removable Drive	CD or DVD drive
USB Port	At least one free USB port